

# Heavy-duty chuck with security function, HSK-A 100, Ø D1: 12 mm



### Order data

Order number	305560 12
GTIN	4062406261245
Item class	31A

### **Description**

#### **Version:**

- · Shanks hard turned (smooth cutting action).
- · Very high clamping force prolongs tool life and improves surface quality.
- · Centred tool clamping with optimum concentricity.
- · Integral length adjustment screw.
- · Internal coolant feed.

#### **Advantage:**

HB (Weldon) flat provides quick and easy protection against the milling cutter pulling out. Positive connection between the milling cutter and arbor. Compact vibration-optimised contour.

#### **Application:**

For clamping tools with parallel shank and HB flat. Ideally suited for heavy-duty machining (HPC, TPC).

### **Supplied with:**

Clamping nut.

## **Optional extras:**

Coolant tube No. 309880. Machining strategy: HPC

Overhang dimension A: 99 mm

Collet outer Ø D: 40 mm

Clamping force up to: 430 Nm

Suitable C-hook (pin) spanner No. 628400: 40/42

# **Technical description**



Suitable C-hook (pin) spanner No. 628400	40/42
Collet outer Ø D	40 mm
Overhang dimension A	99 mm
Clamping Ø D <sub>1</sub>	12 mm
Clamping force up to	430 Nm
Adapter	HSK-A 100
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	Α
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 5 µm
Machining strategy	HPC
Type of product	Heavy-duty chuck

# **Accessories**

HSK coolant tube for HSK 100 309880 100