

**HOLEX**

## Face mill arbor with cooling channel bore, HSK-A 100 A = 100, Spigot Ø d1: 32 mm



### Order data

Order number	306687 32
GTIN	4045197954367
Item class	32A

### Description

#### Version:

- **Clamping Ø 40 with 4 tapped holes for drive blocks to DIN 2079.**
- **With Balluffchip bore.**
- **Increased collar contact surface.**
- **HSK mating faces machined.**

With **cooling channel bores.**

#### Application:

For clamping shell end mills and milling cutter heads.

#### Supplied with:

Lock screw.

#### Optional extras:

Coolant tube No. 309880, socket wrench for coolant tubes No. 309890, toggle spanner No. 309840.

External Ø D: 78 mm

Milling mandrel length L<sub>4</sub>: 24 mm

Spare milling cutter lock screw No. 309860: 32

### Technical description

Milling mandrel length L <sub>4</sub>	24 mm
External Ø D	78 mm

Spare milling cutter lock screw No. 309860	32
Suitable toggle spanner No. 309840	32
Adapter	HSK-A 100 A = 100
Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-3
Arbor standard	DIN 69893
Shape	A
Cooling channel bore	not pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 μm
Machining strategy	HPC
Type of product	Milling head arbor