

Garant
Arbor for screw-in milling cutters with thread tapered form, HSK-A 63, Thread M × Length L1: M8X25

Order data

Order number	307044 M8X25
GTIN	4062406106744
Item class	31A

Description
Version:

Tapered design.
With Balluffchip bore.

Application:

To take screw-in milling cutters with thread.

Optional extras:

Extensions No. 301358, reducers No. 301359, coolant pipe No. 309880, socket for coolant pipe No. 309890.

Note:

Densimet arbors and solid carbide extensions for threaded copy milling cutters, see No. 301373 – 1379 and No. 301362 – 1368.

Machining strategy: HSC

Overhang dimension A: 51 mm

Bore Ø D₁: 8.5 mm

Ø D₂: 13 mm

External Ø D: 15 mm

Reach L₁: 25 mm

L₂: 5 mm

Technical description

Thread M	M8x25
Reach L ₁	25 mm

Overhang dimension A	51 mm
L ₂	5 mm
Bore Ø D ₁	8.5 mm
Ø D ₂	13 mm
External Ø D	15 mm
Adapter	HSK-A 63
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Threaded copy mill arbor