

## Garant

### Arbor for screw-in milling cutters with thread tapered form, HSK-A 100, Thread M × Length L1: M10X150



#### Order data

Order number	307046 M10X150
GTIN	4062406106959
Item class	31A

#### Description

##### Version:

Tapered design.  
With Balluffchip bore.

##### Application:

To take screw-in milling cutters with thread.

##### Optional extras:

Extensions No. 301358, reducers No. 301359, coolant pipe No. 309880, socket for coolant pipe No. 309890.

##### Note:

Densimet arbors and solid carbide extensions for threaded copy milling cutters, see No. 301373 – 1379 and No. 301362 – 1368.

Machining strategy: HSC

Overhang dimension A: 179 mm

Bore  $\varnothing D_1$ : 10.5 mm

$\varnothing D_2$ : 18 mm

External  $\varnothing D$ : 36.5 mm

Reach  $L_1$ : 150 mm

$L_2$ : 10 mm

#### Technical description

Bore $\varnothing D_1$	10.5 mm
Overhang dimension A	179 mm

Ø D <sub>2</sub>	18 mm
Reach L <sub>1</sub>	150 mm
Thread M	M10×150
L <sub>2</sub>	10 mm
External Ø D	36.5 mm
Adapter	HSK-A 100
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Threaded copy mill arbor