



## HD chuck short, slim, HSK-A 100, Clamping range $\varnothing$ D1: 10 mm



### Order data

Order number	307517 10
GTIN	4062406242060
Item class	32A

### Description

#### Version:

- Axial length adjustment, adjustment travel 10 mm.
- With Balluffchip bore.

#### Application:

- For drilling, reaming, and milling.

#### Optional extras:

Reducer sleeves No. 302135 – 302180, Coolant pipe No. 309880, Coolant pipe wrench No. 309890, Parallel wipers No. 343720.

#### Note:

A-dimension = 200 mm available on request!

Overhang dimension A: 90 mm

$\varnothing$  D<sub>2</sub>: 30 mm

External  $\varnothing$  D: 50 mm

L<sub>3</sub>: 42 mm

Adjustment travel V: 10 mm

Thread M: M8×1

### Technical description

Adjustment travel V	10 mm
$\varnothing$ D <sub>2</sub>	30 mm

Overhang dimension A	90 mm
Thread M	M8×1
External Ø D	50 mm
L <sub>3</sub>	42 mm
Clamping Ø D <sub>1</sub>	10 mm
Adapter	HSK-A 100
Arbor standard	DIN 69882-7
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Through-coolant	yes, with max. 80 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Hydraulic clamping chuck

## Accessories

Parallel wiper Plastic Pin Ø 10 mm	343720 10
------------------------------------	-----------