



HD chuck short, slim, HSK-A 100, Clamping range \varnothing D1: 16 mm



Order data

Order number	307517 16
GTIN	4062406242084
Item class	32A

Description

Version:

- Axial length adjustment, adjustment travel 10 mm.
- With Balluffchip bore.

Application:

- For drilling, reaming, and milling.

Optional extras:

Reducer sleeves No. 302135 – 302180, Coolant pipe No. 309880, Coolant pipe wrench No. 309890, Parallel wipers No. 343720.

Note:

A-dimension = 200 mm available on request!

Overhang dimension A: 100 mm

\varnothing D₂: 38 mm

External \varnothing D: 50 mm

L₃: 53 mm

Adjustment travel V: 10 mm

Thread M: M12×1

Technical description

Thread M	M12×1
Overhang dimension A	100 mm

External Ø D	50 mm
Adjustment travel V	10 mm
L ₃	53 mm
Clamping Ø D ₁	16 mm
Ø D ₂	38 mm
Adapter	HSK-A 100
Arbor standard	DIN 69882-7
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Through-coolant	yes, with max. 80 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HSC
Type of product	Hydraulic clamping chuck

Accessories

Parallel wiper Plastic Pin Ø 16 mm	343720 16
------------------------------------	-----------