



HD chuck short, slim, HSK-A 100, Clamping range \varnothing D1: 8 mm



Order data

Order number	307517 8
GTIN	4062406242053
Item class	32A

Description

Version:

- Axial length adjustment, adjustment travel 10 mm.
- With Balluffchip bore.

Application:

- For drilling, reaming, and milling.

Optional extras:

Reducer sleeves No. 302135 – 302180, Coolant pipe No. 309880, Coolant pipe wrench No. 309890, Parallel wipers No. 343720.

Note:

A-dimension = 200 mm available on request!

Overhang dimension A: 75 mm

\varnothing D₂: 28 mm

External \varnothing D: 50 mm

L₃: 26 mm

Adjustment travel V: 10 mm

Thread M: M6

Technical description

L ₃	26 mm
Overhang dimension A	75 mm

Clamping $\varnothing D_1$	8 mm
External $\varnothing D$	50 mm
Thread M	M6
Adjustment travel V	10 mm
$\varnothing D_2$	28 mm
Adapter	HSK-A 100
Arbor standard	DIN 69882-7
Arbor standard	ISO 12164-1
Arbor standard	DIN 69893
Shape	A
Through-coolant	yes, with max. 80 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	$\leq 3 \mu\text{m}$
Machining strategy	HSC
Type of product	Hydraulic clamping chuck

Accessories

Parallel wiper Plastic Pin $\varnothing 8 \text{ mm}$	343720 8
---	----------