Garant

Short drill chuck Form A, HSK-A 63, Clamping range: 1-16 mm



Order data

Order number	307725 1-16
GTIN	4045197931887
Item class	31B

Description

Version:
Concentricity ≤ 20 µm.
With through coolant feed up to max. 50 bar.
· **For clockwise and anticlockwise rotation.**
· **With Ballufchip bore.**
· **Slim design.**
· **Specific coolant transfer to tools with IC.**
· **Optimum holding torques at the tool.**
Supplied with:
Clamping wrench with T-handle.
Optional extras:
Socket wrench No. 309890. Coolant tube No. 309880.
Type: slim
Overhang dimension A: 104 mm
External ⌀ D: 50 mm
Spare Torx® chuck key No. 625220: TX25

Technical description

Clamping range	1 - 16 mm
External ⌀ D	50 mm
Type	slim
Overhang dimension A	104 mm

Spare Torx® chuck key No. 625220	TX25
Adapter	HSK-A 63
Arbor standard	ISO 12164-1
Arbor standard	DIN 69882-7
Arbor standard	DIN 69893-1
Shape	A
Through-coolant	yes, with max. 50 bar
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 20 µm
maximum tightening torque $M_{d\ max}$	≤ 14 Nm
Type of product	Short drill chuck