

Garant
Face mill arbor with cooling channel bores, PSC 40 short, Spigot Ø d1: 16 mm

Order data

Order number	308543 16
GTIN	4062406243807
Item class	31A

Description
Version:

- **With Balluffchip bore.**
- **All shanks hard turned (for smooth running!).**
- **Mating faces of the PSC internal contour machined.**

Application:

For holding shell end mills and face mills with cross keyway.

Supplied with:

Lock screw.

Optional extras:

Coolant tube and assembling key for coolant tubes No. 309885; 309893.

Toggle spanner No. 309840, cutter lock screw No. 309860.

Machining strategy: HPC

Overhang dimension A: 32 mm

External Ø D: 38 mm

Spare milling cutter lock screw No. 309860: 16

Technical description

Spare milling cutter lock screw No. 309860	16
External Ø D	38 mm
Suitable toggle spanner No. 309840	16

Overhang dimension A	32 mm
Spigot $\varnothing d_1$	16 mm
Adapter	PSC 40 short
Arbor standard	ISO 26623-2
Cooling channel bore	pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	$\leq 6 \mu\text{m}$
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Toggle spanner for mandrel $\varnothing 16 \text{ mm}$	309840 16
--	-----------