

Garant
Face mill arbor with cooling channel bores, PSC 40 short, Spigot Ø d1: 22 mm

Order data

Order number	308543 22
GTIN	4062406243814
Item class	31A

Description
Version:

- **With Balluffchip bore.**
- **All shanks hard turned (for smooth running!).**
- **Mating faces of the PSC internal contour machined.**

Application:

For holding shell end mills and face mills with cross keyway.

Supplied with:

Lock screw.

Optional extras:

Coolant tube and assembling key for coolant tubes No. 309885; 309893.

Toggle spanner No. 309840, cutter lock screw No. 309860.

Machining strategy: HPC

Overhang dimension A: 25 mm

External Ø D: 40 mm

Spare milling cutter lock screw No. 309860: 22

Technical description

External Ø D	40 mm
Spare milling cutter lock screw No. 309860	22
Overhang dimension A	25 mm

Suitable toggle spanner No. 309840	22
Spigot Ø d ₁	22 mm
Adapter	PSC 40 short
Arbor standard	ISO 26623-2
Cooling channel bore	pluggable
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 6 µm
Machining strategy	HPC
Type of product	Milling head arbor

Accessories

Toggle spanner for mandrel Ø 22 mm	309840 22
------------------------------------	-----------