

**Garant**
**Boring bar stabiliser 3×D mini, Type: 10R**

**Order data**

Order number	319454 10R
GTIN	4062406308834
Item class	31V

**Description**
**Version:**

Base body of high-quality tool steel, surface and functional faces hardened.

**Advantage:**

Reduces oscillation and vibration when used with all types of boring bars.

**Suitable for :**

All popular boring bars.

**Note:**

To determine the right type of boring bar stabiliser, it is essential to perform a collision check using the Hoffmann e-Tool data from the eShop or via the ToolScout! We recommend a maximum overhang length of 3×D of the types of boring bar used.

Vibration: damped

Cutting direction: right-hand

Clamping  $\varnothing D_1$ : 10 mm

Shank  $\varnothing D_2$ : 32 mm

$\varnothing D_3$ : 40 mm

Overhang  $L_1$ : 30 mm

Shank length  $L_3$ : 53 mm

**Technical description**

Radius R	1.2 mm
Offset Z to the axis	8 mm
Overhang $L_1$	30 mm

Shank $\varnothing D_2$	32 mm
Shank length $L_s$	53 mm
Clamping $\varnothing D_1$	10 mm
Overall length $L_2$	89 mm
C	1 mm
$\varnothing D_3$	40 mm
Cutting direction	right-hand
Boring depth up to	3xD
Vibration	damped
Type of product	Boring bar stabiliser