

Garant
Boring bar stabiliser 3xD mini, Type: 16R

Order data

Order number	319454 16R
GTIN	4062406308872
Item class	31V

Description
Version:

Base body of high-quality tool steel, surface and functional faces hardened.

Advantage:

Reduces oscillation and vibration when used with all types of boring bars.

Suitable for :

All popular boring bars.

Note:

To determine the right type of boring bar stabiliser, it is essential to perform a collision check using the Hoffmann e-Tool data from the eShop or via the ToolScout! We recommend a maximum overhang length of 3xD of the types of boring bar used.

Vibration: damped

Cutting direction: right-hand

Clamping $\varnothing D_1$: 16 mm

Shank $\varnothing D_2$: 32 mm

$\varnothing D_3$: 40 mm

Overhang L_1 : 48 mm

Shank length L_3 : 53 mm

Technical description

Clamping $\varnothing D_1$	16 mm
$\varnothing D_3$	40 mm
Offset Z to the axis	12.5 mm

Radius R	1.2 mm
Overall length L ₂	107 mm
C	1 mm
Overhang L ₁	48 mm
Cutting direction	right-hand
Shank Ø D ₂	32 mm
Shank length L _s	53 mm
Boring depth up to	3×D
Vibration	damped
Type of product	Boring bar stabiliser