



Revolving lathe centre 60°, Morse taper: 6



Order data

Order number	320672 6
GTIN	4062406200251
Item class	32L

Description

Version:

- **Body and live centre hardened.**
- **Live centre through hardened, multiple regrinding possible.**
- **Precision roller bearings for high concentricity.**
- **Maintenance-free due to lifetime lubrication.**
- **Special seal prevents ingress of dirt and coolant.**
- **Point angle 60°.**

Description:

Lathe centres are mainly used on lathes to support long and slim workpieces, since with these workpieces there would otherwise be a risk of the workpiece bending or moving around as a result of the forces generated.

The lathe centre is secured with a Morse taper. The workpiece is clamped in the chuck and a counterbore is added using a centre drill. After re-clamping, the lathe centre is then inserted.

Application:

For all types of lathe, equally suitable for roughing and finish turning.

Body Ø D: 105 mm

Reach B: 149 mm

largest centre point Ø 60° A: 50 mm

maximum radial run-out: 0.01 mm

Centre point length C: 57.5 mm

maximum speed: 2800 rpm

Technical description

for workpiece weight	3500 kg
----------------------	---------

Centre point length C	57.5 mm
Reach B	149 mm
maximum radial run-out	0.01 mm
largest centre point \varnothing 60° A	50 mm
Morse taper	6
Body \varnothing D	105 mm
maximum speed	2800 rpm
Type of product	Centring drill