

Garant**Synchro tool head for ER32, Tap shank Ø d2: 12 mm****Order data**

Order number	338186 12
GTIN	4062406103699
Item class	31P

Description**Version:**

- Tapping and thread forming on machines with synchronised spindles.
- Minimum Length Adjustment: +0.5mm / -0.2 mm.
- Compensation for synchronisation errors, hence better thread quality and clear increase in tool life.
- For collet chucks and driven tools to ISO 15488 (DIN 6499).
- Suitable for left-hand and right-hand threads.

Standard:

- Minimum Length Adjustment: +0.5mm / -0.2 mm.
- Compensation for synchronisation errors, hence better thread quality and clear increase in tool life.

Suitable for :

ER synchro collet No. 338180.

Through-coolant: yes, with max. 50 bar

Ø D₂: 25 mm

for tap shank Ø d₂ DIN 371: M12

for tap shank Ø d₂ DIN 374/376: M16

Overhang L₁: 37 mm

Shank square: 9 mm

Technical description

Shank square	9 mm
Overhang L ₁	37 mm

for tap shank Ø d ₂ DIN 371	M12
for tap shank Ø d ₂ DIN 374/376	M16
Ø D ₂	25 mm
Through-coolant	yes, with max. 50 bar
Type of product	Tapping head accessories