

Garant
Synchro tool head for ER32, Tap shank \varnothing d2: 8 mm

Order data

Order number	338186 8
GTIN	4062406103651
Item class	31P

Description
Version:

- **Tapping and thread forming on machines with synchronised spindles.**
- **Minimum Length Adjustment: +0.5mm / -0.2 mm.**
- **Compensation for synchronisation errors, hence better thread quality and clear increase in tool life.**
- **For collet chucks and driven tools to ISO 15488 (DIN 6499).**
- **Suitable for left-hand and right-hand threads.**

Standard:

- **Minimum Length Adjustment: +0.5mm / -0.2 mm.**
- **Compensation for synchronisation errors, hence better thread quality and clear increase in tool life.**

Suitable for :

ER synchro collet No. 338180.

Through-coolant: yes, with max. 50 bar

 \varnothing D₂: 25 mm

 for tap shank \varnothing d₂ DIN 371: M8

 for tap shank \varnothing d₂ DIN 374/376: M11

 Overhang L₁: 37 mm

Shank square: 6.2 mm

Technical description

Shank square	6.2 mm
Overhang L ₁	37 mm

for tap shank $\varnothing d_2$ DIN 374/376	M11
for tap shank $\varnothing d_2$ DIN 371	M8
$\varnothing D_2$	25 mm
Through-coolant	yes, with max. 50 bar
Type of product	Tapping head accessories