



Stationary machine vice, Type: 150M



Order data

Order number	362175 150M
GTIN	4062406384081
Item class	32P

Description

Version:

Sturdy base body of cast iron, slides and base area hardened. Coolant holes in the base body for good flow of chips. Less component lift-off thanks to special transfer of force in the mobile jaw.

Application:

Versatile clamping unit for machining centres.

Supplied with:

Incl. 2 pcs. top jaws, 2 pcs. front jaws No. 362181 and 1 pc. hand crank.

Optional extras:

Front jaws No. 362177 – 362182, crank No. 362190, spare-parts set No. 362199.

Note:

Alignment dimensions not compatible with those of other manufacturers. Metric version – screws and threads in metric version, drive hexagon = 19 mm AF.

Type: L-keys for hexagonal socket screws

Clamping range b: 0 - 232 mm

Clamping force: 36 kN

Base body height c: 73 mm

Jaw height C: 44.5 mm

Jaw width A: 151 mm

Base body length a: 427 mm

Technical description

L ₁	101.6 mm
----------------	----------

L ₂	58.7 mm
Base body height c	73 mm
Clamping force	36 kN
Colour code for suitable accessories	NC-HOLEX
Type	L-keys for hexagonal socket screws
L ₃	90.5 mm
Base body length a	427 mm
Jaw height C	44.5 mm
Width across flats AF	19 mm
Clamping range b	0 - 232 mm
Jaw width A	151 mm
Base body width B	186 mm
Hole centre spacing f	98.4 mm
Quick adjustment	no
Interchangeable jaws	yes
Type of product	Machine vice

Accessories

Front jaw Standard Type 150	362181 150
Spare-parts set 9 pieces Type 9	362199 9