

Mitutoyo
Digital depth gauge AOS with data output, Measuring range: 300 mm

Order data

Order number	418711 300
GTIN	4946368846460
Item class	44A

Description
Version:

Measured result is displayed in easy-to-read digits. The measuring faces are precision lapped.

Supplied with:

1 battery No. 081560 size 357.

Optional extras:

Data cables No. 497080 and 497100.

Measurement method of the measuring instrument: electro-magnetic inductive procedure

Calibration: A1

Scale divisions: 0.01 mm

Error limit: 0.03 mm

Bridge length: 100 mm

Cross-section measuring beam: 16x3.5 mm

Technical description

Scale divisions	0.01 mm
Calibration	A1
Article no of the battery / rechargeable battery fitted	081560 357
Error limit	0.03 mm
Number of batteries contained	1
Bridge length	100 mm
Cross-section measuring beam	16x3.5 mm
Power supply	Battery-powered

Standard	Manufacturer's standard
Measurement technology	digital
Material	Stainless steel, INOX
all parts	hardened
Packaging	Wallet
Measurement method of the measuring instrument	electro-magnetic inductive procedure
Type of product	DEPTH GAGE, STAINLESS STEEL

Services

Calibration Calipers / depth gauges maximum measuring range 300 mm	011030 300
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	011050 300
Labelling laser-etched Type	018940
DAkkS calibration Calipers / depth gauges maximum measuring range 300 mm	021010 300
Calibration Calipers / depth gauges maximum measuring range 300 mm	021000 300