

**Mitutoyo****External blade micrometer, Measuring range: 0-25 mm****Order data**

Order number	421896 0-25
GTIN	4946368847313
Item class	44A

**Description****Version:**

With non-rotating spindle and flat blade anvils. Measuring spindle and anvil of hardened steel, controls and reading parts satin chrome-plated.

**Supplied with:**

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Scale divisions: 0.01 mm

Spindle Ø: 6.35 mm

Spindle pitch: 0.5 mm

Flat blade anvils width: 0.75 mm

Flat blade anvils length: 6.5 mm

**Technical description**

Spindle Ø	6.35 mm
Calibration	B1
Scale divisions	0.01 mm
Flat blade anvils width	0.75 mm
Measuring range	0 - 25 mm
Spindle pitch	0.5 mm

Flat blade anvils length	6.5 mm
Micrometer barrel graduations	1/50 mm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

### Services

Calibration External tube micrometer maximum measuring range 25 mm	012050 25
DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 25 mm	022000 25
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100