

Mitutoyo**External blade micrometer, Measuring range: 50-75 mm****Order data**

Order number	421896 50-75
GTIN	4946368847337
Item class	44A

Description**Version:**

With non-rotating spindle and flat blade anvils. Measuring spindle and anvil of hardened steel, controls and reading parts satin chrome-plated.

Supplied with:

From size 25-50 including 1 setting standard.

Packaging: sturdy box

Micrometer barrel graduations: 1/50 mm

Calibration: B1

Calibration: B2

Scale divisions: 0.01 mm

Spindle Ø: 6.35 mm

Spindle pitch: 0.5 mm

Flat blade anvils width: 0.75 mm

Flat blade anvils length: 6.5 mm

Technical description

Flat blade anvils width	0.75 mm
Spindle pitch	0.5 mm
Scale divisions	0.01 mm

Flat blade anvils length	6.5 mm
Spindle Ø	6.35 mm
Calibration	B1
Calibration	B2
Micrometer barrel graduations	1/50 mm
Measuring range	50 - 75 mm
Standard	DIN 863
Measurement technology	analogue
Packaging	sturdy box
Type of product	Special external micrometer

Services

DAkkS calibration External micrometer maximum measuring range 100 mm	012060 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	012110 100
Labelling laser-etched Type	018940
Calibration External tube micrometer maximum measuring range 100 mm	012050 100
DAkkS calibration External micrometer maximum measuring range 100 mm	022010 100
Calibration Micrometer standard for external micrometer maximum nominal size 100 mm	022080 100
Calibration External tube micrometer maximum measuring range 100 mm	022000 100