

Kroeplin
Längenmesstechnik**Digital internal quick caliper with long contact points, Measuring range:
30-60 mm****Order data**

| | |
|--------------|---------------|
| Order number | 438979 30-60 |
| GTIN | 2050002053199 |
| Item class | 46Q |

Description**Version:**

1 fixed and 1 movable arm with carbide spherical contact points. **Digital display of the absolute value.**

By entering **preset values**, variations can be determined against any value.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Supplied with 2 batteries No. 081561 size LR3, operating instructions.

Optional extras:

Data cable adapter No. 498954 size A2; data cable No. 497440; radio adapter No. 498954 size A5.

IP Index of Protection: IP 67

Graduations can be switched over: 0.02 mm

Graduations can be switched over: 0.005 mm

Graduations can be switched over: 0.002 mm

Graduations can be switched over: 0.05 mm

Graduations can be switched over: 0.01 mm

Graduations can be switched over: 0.001 mm

Technical description

| | |
|------------------------|-------------|
| Gauging force | 1.3 - 1.8 N |
| IP Index of Protection | IP 67 |

| | |
|---|---------------------------------------|
| Power supply | Battery-powered |
| Repetition accuracy | 0.02 mm |
| maximum groove depth | 8.5 mm |
| Carbide spherical point Ø | 1.5 mm |
| Number of batteries contained | 2 |
| Measuring range | 30 - 60 mm |
| Graduations can be switched over | 0.02 mm |
| Graduations can be switched over | 0.005 mm |
| Graduations can be switched over | 0.002 mm |
| Graduations can be switched over | 0.05 mm |
| Graduations can be switched over | 0.01 mm |
| Graduations can be switched over | 0.001 mm |
| Error limit | 0.04 mm |
| minimum groove width | 2.5 mm |
| Article no of the battery / rechargeable battery fitted | 081561 LR3 |
| maximum contact point length L (measurement depth) | 127 mm |
| Standard | Manufacturer's standard |
| Reversible reading | mm / inch |
| Interface | Bluetooth interface |
| Interface | USB interface |
| Interface | USB interface |
| Measured value saving | Once-off setting of the zero position |
| Measurement technology | digital |
| Calibration | C7 |
| Type of product | Internal quick calipers |

Services

| | |
|---|--------|
| Labelling laser-etched Type | 018940 |
| Calibration External / internal quick caliper | 013850 |

| | |
|--|----------|
| DAkkS calibration External / internal quick caliper | 011320 |
| Calibration External / internal quick caliper Type S | 023450 S |
| DAkkS calibration External / internal quick caliper Type S | 023460 S |

Accessories

| | |
|---|------------|
| Transmitter Type S2 | 498966 S2 |
| Receiver / USB keyboard interface Type | 498965 |
| Alkaline-manganese batteries International size LR3 | 081556 LR3 |
| Multi-receiver / USB keyboard interface Type | 498975 |