

Ceramic gauge block Tolerance class 1, Nominal size: 1,9 mm



Order data

| Order number | 481060 1,9 |
|--------------|---------------|
| GTIN | 4045197154347 |
| Item class | 41L |

Description

Version:

Made of high purity zirconium oxide ceramic material (ZrO_2). Version same as No. 481250. All gauge blocks are marked with an individual identification number. < CRLF>Size 0.5 to 10 − cross section = 30×9 mm. < CRLF>Size 11 to 500 − cross section = 35×9 mm.

 Tolerance class 1 as working and setting blocks for manufacturing and for checking inspection gauges.

Made of high purity industrial ceramic (Zirconium Dioxide ZrO₂).

Advantage:

Ideal for daily use in manufacture:

- · Stainless.
- No need to degrease before use.
- · No need to grease after use.
- · Insensitive to shock and impact.
- · Twice as hard as steel.
- · 10 times higher wear resistance.
- · Highly resistant to alkalis, acids, oil and grinding water.
- Non-magnetic.
- · Cannot cold weld.
- · Low thermal conductivity.

Note:

Further sizes and accuracies on request.



Technical description

| Nominal size | 1.9 mm |
|-----------------|--|
| Standard | DIN EN ISO 3650 |
| Tolerance class | 1 |
| Material | Zirconium Oxide (ZrO2) ceramic material |
| Calibration | L2 |
| Type of product | Parallel gauge block |

Services

| Calibration Gauge block steel / ceramic maximum length 100 mm | 018140 100 |
|--|------------|
| DAkkS calibration Ceramic gauge block maximum length 100 mm | 018200 100 |
| Calibration Gauge block steel / ceramic maximum length 100 mm | 028060 100 |
| DAkkS calibration Ceramic gauge block maximum length 100 mm | 028150 100 |