Garant

Polishing point 400 grit (white) super-fine, Head Ø×length: 8X10 mm

Order data

Order number	551923 8X10
GTIN	4062406572525
Item class	51E

Description

Version:
Polishing points with **standard aluminium oxide (A)** in resilient rubber bonding.
GARANT polishing points are characterised by long service life and quick production of fine, even surface finishes. Finest polishing grades or surfaces right up to mirror finish can be achieved, depending on the version used. GARANT polishing points can be profiled using dressing sticks.
Application:
For fine abrasion and polishing of steel, stainless and acid-resistant steel, high-temperature materials and non-ferrous metals. Polishing grinding points do not clog even when used on materials prone to clogging. For matt finish or application of visual effects on stainless containers etc. **Due to resilient bonding of abrasive grit a very fine polish is achieved.**
Not suitable for sharp edges and rough surfaces.
Grinding medium code: ZC
Shape description: cylindrical
Head Ø: 8 mm
Head length: 10 mm
Shank Ø: 3 mm
recommended circumferential speed: 10 - 15 m/s

Technical description

Shape description	cylindrical
Head ∅	8 mm
Grit	400
Shank ∅	3 mm
recommended circumferential speed	10 - 15 m/s
Head length	10 mm
Grinding media	Standard aluminium oxide (A)
Grinding medium code	ZC
Colour	orange
Type of product	Polishing points