

**Coarse cleaning disc with shank (SiC), XT-ZS, Disc Ø: 75 mm****Order data**

Order number	555930 75
GTIN	4054596605817
Item class	53M

Description**Version:**

Coarse cleaning disc with synthetic nylon fleece evenly impregnated with abrasive grit on glass fibre pad. Open structure, will not clog.

Stable edge, extremely high material removal rate and service life. Ideal for removal of scale.

Application:

For radial use on flexible shafts and straight die grinders. For rust removal, paint removal, dressing weld seams and removing surface dirt.

Iron, sulphur and chlorine constituents: < 0.1 %

Grit designation: extra coarse

Thickness: 15 mm

Shank Ø: 6 mm

recommended speed: 8000 rpm

Technical description

Disc thickness	15 mm
Disc Ø	75 mm
recommended speed	8000 rpm

Thickness	15 mm
Shank Ø	6 mm
Grinding media	Silicon carbide (SiC)
Grinding medium code	SiC
Degree of hardness	very hard
Grit designation	extra coarse
Iron, sulphur and chlorine constituents	< 0.1 %
Product name attribute	XT-ZS
Type of product	Rough cleaning non-woven abrasive mesh

Accessories

Mandrel Number of discs to be clamped 1	556380 1
Mandrel Number of discs to be clamped 1-2	556380 1-2