

## Combination spanner, long version, Width across flats: 13 mm



### **Order data**

Order number	614600 13
GTIN	4062406220648
Item class	61A

## **Description**

#### **Version:**

Drop-forged. With close tolerance jaw width.

With easy-grip profile shaft. Exceptional tool life and wear resistance. Ring end deep cranked.

#### Standard:

#### DIN 3113 B / ISO 3318 / ISO 7738

#### **Material:**

Chrome alloy steel; non-flaking chrome-plated, smoothed finish.

#### Note:

**HT-Drive** – the special profile. An extremely accurately fitting profile - developed for aviation and aerospace. Tools with this profile can be recognised by the **HT-Drive** symbol. **Advantages:** 

- · Bolts are gripped on the flanks. The bolts are protected. Longer bolt life.
- · Larger contact surfaces between bolt and tool. Secure grip and higher torque transmission.

Spanner length L: 195 mm maximum jaw height h1: 6.5 mm maximum ring height h<sub>2 max</sub>: 10 mm

# **Technical description**

maximum jaw height h1	6.5 mm
maximum ring height h <sub>2 max</sub>	10 mm
Width across flats	metric
Width across flats	13 mm
Spanner length L	195 mm

Ring setting	10 degrees
Manufacturing process	drop forged
Material	Chrome alloy steel
Surface	chromium-plated over nickel
non-sparking	no
Ring end deep cranked	yes
Type of product	Spanner