Garant

Double-ended ring spanner, deeply cranked, Width across flats: 36X41 mm



Order data

Order number	615600 36X41
GTIN	4062406221102
Item class	61A

Description

Version:
Drop-forged. With close tolerance jaw widths.
With easy-grip profile shaft. Exceptional tool life and wear resistance. Ring ends with **HT-Drive** profile.
Standard:
DIN 838 / ISO 3318
Material:
Chrome alloy steel; non-flaking chrome-plated, smoothed finish.
Note:
HT-Drive – the particularly close-fitting profile.
Advantage
· **Bolts are gripped on the flanks.**
· **The corners are protected.**
· **Longer bolt life.**
· **Larger contact surfaces between bolt and tool.**
· **Secure grip and higher torque transmission.**
Spanner length L: 440 mm
maximum ring ⌀ D_1 max: 53 mm
maximum ring ⌀ D_2 max: 60 mm

Technical description

Width across flats 1	36 mm
maximum ring ⌀ D_2 max	60 mm
Width across flats	metric

Width across flats 2	41 mm
maximum ring Ø D_1 max	53 mm
Spanner length L	440 mm
Ring setting	75 degrees
Manufacturing process	drop forged
Material	Chrome vanadium steel
Surface	matt chrome-plated
Ring end deep cranked	yes
open ring	no
Type of product	Spanner