

# **BOSCH**

# Cordless drill/driver with exchangeable drill chuck, Type: GSR1215FC



### **Order data**

Order number	070242 GSR1215FC
GTIN	3165140847322
Item class	03B

### Description

#### **Version:**

Bosch cordless drill / driver

- · Compact, powerful 12 V cordless drill with forward/reverse operation.
- · With Electronic Motor Protection (EMP) and Electronic Cell Protection (ECP).
- · LED light to illuminate the working area and battery charge display.
- · Multi-stage torque setting for precise screw driving.
- · Electronic speed control for precise drilling and screw driving.
- · Softgrip.

Precise operation even where access is difficult due to compact size **with bit holder** or interchangeable **angle drilling attachment or eccentric drilling attachment,.** Flexible working thanks to the quick-change system with four different **FlexiClick**-heads. Comfortable to use: Attachments remain for simply setting 16 different positions on the device.

#### **Supplied with:**

Supplied with  $2 \times 12 \text{ V} / 2.0 \text{ Ah Li-ion battery, charger, eccentric drilling attachment, drill chuck, angle drilling attachment, bit holder.$ 

#### Attention:

German version. Order free UK adapter plug No. 08 1172\_GB.

#### Note:

See No. 073852 ff and 073866 for suitable spare batteries and chargers.

Packaging: Modular case (L-Boxx)

suitable battery - supplier / battery type / voltage: Bosch 12 V



Manufacturer's designation: GSR 12V-15FC

Motor design: 2-pole motor

Number of rechargeable batteries contained: 2

Battery capacity: 2 A·h Battery voltage: 12 V

maximum torque soft: 15 N·m

# **Technical description**

maximum torque hard	30 N·m
Weight	0.8 kg
maximum vibration to EN	< 1.9 m/s <sup>2</sup>
suitable battery - supplier / battery type / voltage	Bosch 12 V
Battery capacity	2 A·h
maximum torque soft	15 N·m
Speed range 2nd speed	0 - 1300 rpm
Packaging	Modular case (L-Boxx)
maximum twist drill size Ø in wood	19 mm
Speed range 1st speed	0 - 400 rpm
maximum twist drill size Ø in steel	10 mm
Quick-clamping chuck range	0 - 10 mm
Manufacturer's designation	GSR 12V-15FC
Motor design	2-pole motor
Battery voltage	12 V
typical application	Strong
Number of rechargeable batteries contained	2

## **Accessories**

Battery charger Type AL1130CV	073866 AL1130CV
Li-ion battery Battery type, battery voltage B12 V	073851 B12