



Torque shut-off screwdriver with ParameterControl Baton offset screwdriver, Type: 71126260



Order data

Order number	071120 71126260
GTIN	4014586883830
Item class	03F

Description

Version:

FEIN ACCU TEC shut-off screwdrivers are designed for the most demanding applications requiring **precise screw tightening in series production**.

- **Brushless EC motors with working life extended by a factor of several times and up to 80 % lower maintenance costs.**
- **Restart delay after the screw tightening, to avoid "follow-up".**
- **Restart inhibit if the remaining battery charge is insufficient to perform the screw tightening.**
- **Tight screw tightening tolerances for high screw tightening quality.**
- **Precise and consistent tightening torques in any screw tightening application.**
- **Testable screwdrivers, CmK-value > 1.67 ±10% (based on 6 sigma) to ISO 5393 VDI/VDE 2647.**

The release torque is 25 % above the tightening torque.

Torque shut-off screwdriver with ParameterControl for easy and individual programming on a PC , using the programming adaptor (No. 071135 size 92604163).

Freely programmable parameters: Speed, direction of rotation, angle of rotation, torque threshold and time.

Up to 5 programmable steps. Precise configuration for each screw tightening application. **Final switch-off by mechanical clutch.** Ideal for optimising the process and time.

Shut-off screwdriver, takes a Li-ion battery. Maintenance-free up to 500,000 screw fastenings.

Supplied with:

Just the screwdriver itself is supplied, **without battery, charger or setting tool and angle head**. Please order the battery, charger, setting tool and angle head specifically for the device.

Note:

See 073832 ff. for suitable batteries and chargers.

See no. 654300 ff. for

torque analysers; see no. 654381 for torque sensors/rotational angle sensors.

Calibration service on request.

suitable battery - supplier / battery type / voltage: Fein type E 12 V

suitable battery - supplier / battery type / voltage: Fein type E 18 V

Manufacturer's designation: ASW 18-30 PC

Battery voltage: 12 V

Battery voltage: 18 V

Torque range: 12 - 30 Nm

Speed range: 30 - 420 rpm

Format: Baton offset screwdriver

Technical description

Manufacturer's designation	ASW 18-30 PC
Speed range	30 - 420 rpm
Weight including rechargeable battery	1.7 kg
Motor design	Brushless EC motor
Torque range	12 - 30 Nm
Battery voltage	12 V
Battery voltage	18 V
Format	Baton offset screwdriver
suitable angle head	071133 15010
suitable battery - supplier / battery type / voltage	Fein type E 12 V
suitable battery - supplier / battery type / voltage	Fein type E 18 V
Type of rechargeable battery	Lithium-ion
Power supply	Rechargeable battery-powered
Type of product	Screwdriver

Accessories

Battery charger Type FE30	073845 FE30
Battery charger Type FE50	073845 FE50
Li-ion battery Battery type, battery voltage FE18 V	073838 FE18
Angle head for ASW 18 Type 26020	071133 26020
ACCU TEC setting tool Type ESTW	071119 ESTW
Programming adaptor Type 92604163	071135 92604163
Electronic torque tool tester "TTT"	654340
Li-ion battery Rechargeable battery type, battery voltage FE18 V	073835 FE18
Battery charger Type FE80	073845 FE80