

**Hammer drill 230 V, Type: PLH32XE****Order data**

Order number	075520 PLH32XE
GTIN	4002395233342
Item class	03M

Description**Version:**

- **Sturdy hammer drill with pneumatic hammer action**
- **SDS plus chuck.**
- **High-strength metal gearbox casing.**
- **Forward / reverse, hammer action on / off and electronic speed control.**

Mains combination hammer drill with high impact energy for drilling holes up to 32 mm in concrete. Power cable 4 m.

- **FIXTEC tool quick-change system for switching between the SDS-Plus chuck and the quick-release metal drill chuck, without using tools.**
- **Zero rotation for easy chisel work.**
- **Safety clutch protects user and machine if the drill jams.**
- **AVS anti-vibration system.**

Supplied with:

FIXTEC SDS-plus adapter, quick-change chuck 1.5 – 13 mm, additional handle with depth stop, drilling grease, transport case.

Attention:

German version. Order free UK adapter plug No. 08 1172_GB.

Note:

Suitable carbide hammer drills can be found under No. 787000ff.

Suitable spare batteries and chargers can be found under No. 073808ff. and No. 073840.

Packaging: Carrying case

Skaft: SDS Plus

Manufacturer's designation: PLH32XE
Power consumption: 900 W
Speed range: 0 - 800 rpm
maximum twist drill size Ø in steel: 16 mm
maximum twist drill size Ø in wood: 40 mm
maximum twist drill size Ø in concrete: 32 mm

Technical description

Power consumption	900 W
maximum twist drill size Ø in steel	16 mm
Quick-clamping chuck range	1.5 - 13 mm
maximum hammer rate	4500 - 4500 rpm
Manufacturer's designation	PLH32XE
maximum twist drill size Ø in wood	40 mm
Weight	3.6 kg
Tool arbor shape	SDS-Plus
maximum vibration to EN	22 m/s ²
Impact energy	3.8 J
maximum twist drill size Ø in concrete	32 mm
Speed range	0 - 800 rpm
Skaft	SDS Plus
Packaging	Carrying case