



ALZTRONIC bench drill, maximum drill Ø in steel: 12 mm



Order data

Order number	076563 12
GTIN	
Item class	03P

Description

Version:

High-speed, durable and precise bench drill. Multi-touch display with scratch-resistant glass surface for optimum readability. Simple and coherent user guidance via pictograms on display. Digital drill depth display with reference zero orientation.

- · AC motor 230 V, 50 Hz.
- Digital speed display.
- · Manual input of spindle speed (set value).
- · Reversible.
- · Swivelling spindle guard with electrical interlock.
- Mushroom-head pushbutton (latching) for EMERGENCY STOP.
- · 24-month warranty.
- · Without underneath cabinet and without drill chuck.

With height-adjustable and swivelling drill head.

Attention:

German version. Order free UK adapter plug No. 08 1172_GB.

Note:

Plates for other bench drills available on request. Manufacturer's designation: ALZTRONIC i12

Power consumption: 540 W maximum speed: 250 - 5000 rpm



Toolholder: B16

maximum machine tap \emptyset in steel: M10

Spindle stroke: 40 mm

Technical description

Distance spindle-base plate maximum	250 mm
Machine baseplate width of usable area	300 mm
maximum machine tap Ø in steel	M10
Weight	64 kg
Distance spindle-base plate minimum	110 mm
Spindle stroke	40 mm
maximum speed	250 - 5000 rpm
Feed	manual
Throat	200 mm
Number of T-slots	2
Manufacturer's designation	ALZTRONIC i12
Power consumption	540 W
Toolholder	B16
Drill head height adjustment	Handwheel
Machine baseplate height of usable area	240 mm
maximum drill Ø in steel	12 mm
T-slot pitch	80 mm
T-slot nominal size	12 mm
Column Ø	50 mm