

ALZMETALL
we drive productivity

ALZTRONIC bench drill, maximum drill Ø in steel: 6 mm



Order data

Order number	076563 6
GTIN	
Item class	03P

Description

Version:

High-speed, durable and precise bench drill. Multi-touch display with scratch-resistant glass surface for optimum readability. Simple and coherent user guidance via pictograms on display. Digital drill depth display with reference zero orientation.

- **AC motor 230 V, 50 Hz.**
- **Digital speed display.**
- **Manual input of spindle speed (set value).**
- **Reversible.**
- **Swivelling spindle guard with electrical interlock.**
- **Mushroom-head pushbutton (latching) for EMERGENCY STOP.**
- **24-month warranty.**
- **Without underneath cabinet and without drill chuck.**

With height-adjustable and swivelling drill head.

Attention:

German version. Order free UK adapter plug No. 08 1172_GB.

Note:

Plates for other bench drills available on request.

Manufacturer's designation: ALZTRONIC i6

Power consumption: 540 W

maximum speed: 700 - 10000 rpm

Toolholder: B16
 maximum machine tap Ø in steel: M6
 Spindle stroke: 40 mm

Technical description

T-slot pitch	80 mm
maximum drill Ø in steel	6 mm
Power consumption	540 W
maximum machine tap Ø in steel	M6
Weight	64 kg
Drill head height adjustment	Handwheel
Throat	200 mm
Toolholder	B16
Column Ø	50 mm
Feed	manual
maximum speed	700 - 10000 rpm
Distance spindle-base plate maximum	250 mm
Manufacturer's designation	ALZTRONIC i6
Number of T-slots	2
Machine baseplate height of usable area	240 mm
Distance spindle-base plate minimum	110 mm
T-slot nominal size	12 mm
Spindle stroke	40 mm
Machine baseplate width of usable area	300 mm