

ALZMETALL
we drive productivity

ALZTRONIC bench drill, maximum drill Ø in steel: 9 mm



Order data

Order number	076563 9
GTIN	
Item class	03P

Description

Version:

High-speed, durable and precise bench drill. Multi-touch display with scratch-resistant glass surface for optimum readability. Simple and coherent user guidance via pictograms on display. Digital drill depth display with reference zero orientation.

- **AC motor 230 V, 50 Hz.**
- **Digital speed display.**
- **Manual input of spindle speed (set value).**
- **Reversible.**
- **Swivelling spindle guard with electrical interlock.**
- **Mushroom-head pushbutton (latching) for EMERGENCY STOP.**
- **24-month warranty.**
- **Without underneath cabinet and without drill chuck.**

With height-adjustable and swivelling drill head.

Attention:

German version. Order free UK adapter plug No. 08 1172_GB.

Note:

Plates for other bench drills available on request.

Manufacturer's designation: ALZTRONIC i9

Power consumption: 540 W

maximum speed: 390 - 6500 rpm

Toolholder: B16
 maximum machine tap \varnothing in steel: M8
 Spindle stroke: 40 mm

Technical description

Column \varnothing	50 mm
Drill head height adjustment	Handwheel
Power consumption	540 W
Distance spindle-base plate minimum	110 mm
Toolholder	B16
Feed	manual
T-slot nominal size	12 mm
Throat	200 mm
maximum machine tap \varnothing in steel	M8
Distance spindle-base plate maximum	250 mm
maximum speed	390 - 6500 rpm
Weight	64 kg
Machine baseplate height of usable area	240 mm
T-slot pitch	80 mm
Manufacturer's designation	ALZTRONIC i9
Spindle stroke	40 mm
maximum drill \varnothing in steel	9 mm
Machine baseplate width of usable area	300 mm
Number of T-slots	2