



Hydraulic cordless hole punch with matrices, Type: M18HKP-SET



Order data

Order number	078252 M18HKP-SET
GTIN	4002395138920
Item class	03L

Description

Version:

FORCE LOGIC™ **hydraulic 60 kN cordless hole punch** punches holes up to Ø 100 mm in 3mm steel or 2.5 mm stainless steel.

- **With 3/4-16 UNF tapped hole on the device.**
- **Quick-change system with key-less tool change permits punches and matrices to be assembled separately from the tool.**
- **Compatible with commercially-available accessories.**
- **Easily aligned thanks to matrices with cross-hairs.**

Supplied with:

M12-18C charger, carrying case, 1 each pull screw 11.1 mm (7/16-20 UNF) and 19 mm (3/4-16 UNF), Quick-change system with key-less tool change, punches and matrices with UNF threads for hole sizes: M16, M20, M25, M32, M40.

Attention:

German version. Order free UK adapter plug No. 08 1172_GB.

Note:

Suitable sheet metal punches with metric threads No. 834000 ff. (not size 12.5) and the necessary draw bolts 834070 can be found in Product Group 83.

Packaging: Carrying case

suitable battery - supplier / battery type / voltage: Milwaukee type B 18 V

Manufacturer's designation: M18 HKP-SET

Number of rechargeable batteries contained: 1
 Type of rechargeable battery: Lithium-ion
 Battery capacity: 2 A·h
 Battery voltage: 18 V
 Press force: 60 kN

Technical description

maximum diameter	100 mm
Battery capacity	2 A·h
Manufacturer's designation	M18 HKP-SET
suitable battery - supplier / battery type / voltage	Milwaukee type B 18 V
max. punching depth in steel	3 mm
Weight	2.3 kg
Packaging	Carrying case
max. punching depth in stainless steel	2.5 mm
Battery voltage	18 V
Press force	60 kN
Type of rechargeable battery	Lithium-ion
Number of rechargeable batteries contained	1

Accessories

Battery charger Type M1218C	073840 M1218C
Battery charger Type M1218FC	073840 M1218FC
Li-ion system M18B2 Battery type, battery voltage MB18 V	073827 MB18