



Hydraulic cordless crimping tool, Type: M18HCCT



Order data

Order number	078254 M18HCCT
GTIN	4002395138821
Item class	03L

Description

Version:

Compact hydraulic crimping tool suitable for use of cable lugs and connectors from 16 mm² to 300 mm².

- **FORCE LOGIC™ hydraulic 53 kN cordless crimping tool, makes crimped connections in less than 3s.**
- **Optimum balance for proven one-hand operation.**
- **In-Line design and 350° rotating head, ideal for working where access is difficult.**
- **Compatible with ONE KEY™. Data transmission by Bluetooth for reporting the use of the device.**
- **PFM (Predictive Force Monitoring). Automatic adjustment of the crimping pressure on the connectors ensures the optimum crimping pressure for all crimping operation. Visual feedback of full pressure by a green light.**
- **Long-term reliability. Maintenance intervals at 30,000 crimping operations.**
- **Universal capability for all popular U-crimp inserts.**

Supplied with:

M12-18C charger, carrying case.

Attention:

German version. Order free UK adapter plug No. 08 1172_GB.

suitable battery - supplier / battery type / voltage: Milwaukee type B 18 V

App link: OneKey
 Manufacturer's designation: M18 HCCT
 Number of rechargeable batteries contained: 1
 Type of rechargeable battery: Lithium-ion
 Battery voltage: 18 V
 Battery capacity: 2 A·h
 Press force: 53 kN

Technical description

Crimping time	<3 s
Weight including rechargeable battery	3.7 kg
Battery voltage	18 V
Battery capacity	2 A·h
Press force	53 kN
max. cross-section, copper	300 mm ²
max. cross-section, aluminium	150 mm ²
suitable battery - supplier / battery type / voltage	Milwaukee type B 18 V
App link	OneKey
Type of rechargeable battery	Lithium-ion
Number of rechargeable batteries contained	1
Manufacturer's designation	M18 HCCT

Accessories

Battery charger Type M1218FC	073840 M1218FC
Battery charger Type M1218C	073840 M1218C
Li-ion system M18B2 Battery type, battery voltage MB18 V	073827 MB18
Crimping tool insert Standard Cross section 120 mm ²	078285 120
Crimping tool insert Standard Cross section 150 mm ²	078285 150
Crimping tool insert Standard Cross section 16 mm ²	078285 16
Crimping tool insert Standard Cross section 185 mm ²	078285 185

Crimping tool insert Standard Cross section 240 mm ²	078285 240
Crimping tool insert Standard Cross section 25 mm ²	078285 25
Crimping tool insert Standard Cross section 300 mm ²	078285 300
Crimping tool insert Standard Cross section 35 mm ²	078285 35
Crimping tool insert Standard Cross section 50 mm ²	078285 50
Crimping tool insert Standard Cross section 70 mm ²	078285 70
Crimping tool insert Standard Cross section 95 mm ²	078285 95
Crimping tool insert DIN CU Cross section 120 mm ²	078286 120
Crimping tool insert DIN CU Cross section 150 mm ²	078286 150
Crimping tool insert DIN CU Cross section 16 mm ²	078286 16
Crimping tool insert DIN CU Cross section 185 mm ²	078286 185
Crimping tool insert DIN CU Cross section 240 mm ²	078286 240
Crimping tool insert DIN CU Cross section 25 mm ²	078286 25
Crimping tool insert DIN CU Cross section 300 mm ²	078286 300
Crimping tool insert DIN CU Cross section 35 mm ²	078286 35
Crimping tool insert DIN CU Cross section 50 mm ²	078286 50
Crimping tool insert DIN CU Cross section 70 mm ²	078286 70
Crimping tool insert DIN CU Cross section 95 mm ²	078286 95