



Heat gun, Type: 006464



Order data

Order number	078321 006464
GTIN	4007841006464
Item class	07E

Description

Version:

Electronically controlled heat gun HG 2120 E, temperature steplessly adjustable from 80 – 630°C, air volume can be adjusted in 3 stages from 150 – 500 ltr/min.

Application:

For welding and forming plastics, for shrinking, removing paints, soldering, drying, and thawing.

Supplied with:

Heat gun No. 078321 size 351403, wide angle nozzle 50 mm, reducer nozzle, reflector nozzle, 100-piece shrink sleeve set.

Attention:

German version. Order free UK adapter plug No. 08 1172_GB.

Packaging: transport suitcase

Manufacturer's designation: HG 2120EKF

Power consumption: 2200 W

Air temperature: 80 - 630 °C

Air flow volume stage 1: 150 l/min

Air flow volume stage 2: 300 l/min

Air flow volume stage 3: 500 l/min

Technical description

Air flow volume stage 3	500 l/min
Power consumption	2200 W
Air flow volume stage 2	300 l/min
Manufacturer's designation	HG 2120EKF
Air temperature	80 - 630 °C
Version	Set
Weight	850 g
Air flow volume stage 1	150 l/min
Packaging	transport suitcase

Accessories

Heat gun accessory set 12 pieces Type 075569	078329 075569
Temperature scanner HL Scan Type 014919	078326 014919
Temperature scanner HG Scan PRO Type 007553	078325 007553
Temperature scanner HG Scan PRO Type 007690	078325 007690