Atlas Copco

Pneumatic power drill, Type: D2148RQ



Order data

Order number	079051 D2148RQ
GTIN	7322590019785
Item class	03R

Description

Version:

All technical data relate to a dynamic pressure of **6.3 bar** and the specified hose internal Ø. A range of powerful and very smooth running drills with pistol grip and a drilling power of up to 13 mm in steel. Exhaust air is discharged through the handle, to prevent drill chips from swirling up. With quick-release chuck. With changeover valve for **clockwise / anticlockwise rotation** (for use as a screwdriver or tap driver).

Supplied with:

Quick-clamping chuck. Additionally with support handle.

Spare part:

Selected service kits: Sets of replacement parts for most Atlas Copco pneumatic tools can be supplied on request for preventive maintenance and servicing.

Output power: 250 W

maximum speed: 0 - 750 rpm

Quick-clamping chuck range: 1.5 - 13 mm

maximum air consumption: 600 l/min

Connection thread: BSW

Compressed air connection: 1/4 inch

Technical description

Quick-clamping chuck range	1.5 - 13 mm
maximum air consumption	600 l/min
maximum speed	0 - 750 rpm

maximum vibration to EN	3.7 m/s ²
Length	248 mm
Output power	250 W
Weight	1.4 kg
recommended hose size (internal Ø)	10 mm
Operating noise	85 dB(A)
Manufacturer's designation	D2148RQ
Compressed air connection	1/4 inch
Connection thread	BSW
Type of product	Drill