



Pneumatic screwdriver, Type: S2307CE



Order data

Order number	079163 S2307CE
GTIN	7322590038373
Item class	03R

Description

Version:

All technical data relate to a dynamic pressure of **6.3 bar** and the specified hose internal Ø.

- **With slip clutch.**
- **Adjustable torque setting.**
- **Reversible for clockwise/ anticlockwise rotation.**

Particularly suitable for series production screwdriving with quick-release bit holder for E 6.3 bits (see No. 674205 ff). Torque is externally adjustable using a twist sleeve.

Spare part:

Selected service kits: Sets of replacement parts for most Atlas Copco pneumatic tools can be supplied on request for preventive maintenance and servicing.

Torque range: 2,5 – 10 Nm

maximum screw Ø (8.8 - 12.9): M6

maximum speed: 900 rpm

Tool arbor size: 1/4 inch

Format: Pistol

maximum air consumption: 504 l/min

Technical description

Format	Pistol
--------	--------

maximum air consumption	504 l/min
Torque range	2,5 – 10 Nm
Weight	1.2 kg
Manufacturer's designation	S2307CE
Tool arbor size	1/4 inch
Operating noise	82 dB(A)
recommended hose size (internal Ø)	10 mm
maximum speed	900 rpm
maximum vibration to EN	< 2.5 m/s ²
maximum screw Ø (8.8 - 12.9)	M6
Compressed air connection	1/4 inch
Connection thread	BSW
Type of product	Screwdriver