



Pneumatic screwdriver, Type: S2310



Order data

Order number	079163 S2310
GTIN	7322590036980
Item class	03R

Description

Version:

All technical data relate to a dynamic pressure of **6.3 bar** and the specified hose internal Ø.

- **With slip clutch.**
- **Adjustable torque setting.**
- **Reversible for clockwise/ anticlockwise rotation.**

Particularly suitable for series production screwdriving with quick-release bit holder for E 6.3 bits (see No. 674205 ff).

Spare part:

Selected service kits: Sets of replacement parts for most Atlas Copco pneumatic tools can be supplied on request for preventive maintenance and servicing.

Torque range: 2 – 15 Nm

maximum screw Ø (8.8 - 12.9): M8

maximum speed: 800 rpm

Tool arbor size: 1/4 inch

Format: Pistol

maximum air consumption: 510 l/min

Technical description

Operating noise	81 dB(A)
-----------------	----------

maximum vibration to EN	< 2.5 m/s ²
Torque range	2 – 15 Nm
Weight	1.4 kg
maximum air consumption	510 l/min
recommended hose size (internal Ø)	10 mm
maximum screw Ø (8.8 - 12.9)	M8
Tool arbor size	1/4 inch
Format	Pistol
maximum speed	800 rpm
Manufacturer's designation	S2310
Compressed air connection	1/4 inch
Connection thread	BSW
Type of product	Screwdriver