

Pneumatic screwdriver, Type: S2370



Order data

Order number	079163 S2370
GTIN	7322590011420
Item class	03R

Description

Version:

All technical data relate to a dynamic pressure of **6.3 bar** and the specified hose internal \emptyset .

- · With slip clutch.
- · Adjustable torque setting.
- · Reversible for clockwise/ anticlockwise rotation.

Particularly suitable for series production screwdriving with quick-release bit holder for E 6.3 bits (see No. 674205 ff).

Spare part:

Selected service kits: Sets of replacement parts for most Atlas Copco pneumatic tools can be supplied on request for preventive maintenance and servicing.

Torque range: 2 – 6 Nm

maximum screw Ø (8.8 - 12.9): M5 maximum speed: 1300 rpm Tool arbor size: 1/4 inch

Format: Rod

maximum air consumption: 240 l/min

Technical description

maximum screw Ø (8.8 - 12.9)	M5
Manufacturer's designation	S2370
Operating noise	83 dB(A)

recommended hose size (internal Ø)	6.3 mm
Tool arbor size	1/4 inch
Weight	0.9 kg
maximum speed	1300 rpm
Format	Rod
Torque range	2 – 6 Nm
maximum air consumption	240 l/min
maximum vibration to EN	< 2.5 m/s ²
Compressed air connection	1/4 inch
Connection thread	BSW
Type of product	Screwdriver