



Pneumatic shut-off screwdriver, Type: S2416L



Order data

Order number	079165 S2416L
GTIN	7322590017040
Item class	03R

Description

Version:

All technical data relate to a dynamic pressure of **6.3 bar** and the specified hose internal Ø.

- **Precise, non-wearing cut-out clutch.**
- **High torque accuracy.**

Particularly suitable for series production screwdriving with quick-release bit holder for E 6.3 bits (see No. 674200 ff).

Oil-free - no additional pneumatic oiler required.

Spare part:

Selected service kits: Sets of replacement parts for most Atlas Copco pneumatic tools can be supplied on request for preventive maintenance and servicing.

Manufacturer's designation: S2416L

Torque range: 0.5 - 1.6 Nm

maximum screw Ø (8.8 - 12.9): M3

maximum speed: 1500 rpm

Tool arbor size: 1/4 inch

Format: Rod

Technical description

recommended hose size (internal Ø)	10 mm
maximum air consumption	360 l/min
Manufacturer's designation	S2416L

Tool arbor size	1/4 inch
Torque range	0.5 - 1.6 Nm
maximum screw \varnothing (8.8 - 12.9)	M3
Weight	0.9 kg
maximum vibration to EN	$< 2.5 \text{ m/s}^2$
Format	Rod
Operating noise	73 dB(A)
maximum speed	1500 rpm
Compressed air connection	1/4 inch
Connection thread	BSW
Type of product	Screwdriver