



Pneumatic shut-off screwdriver, Type: S2450P



Order data

Order number	079165 S2450P
GTIN	7322590017057
Item class	03R

Description

Version:

All technical data relate to a dynamic pressure of **6.3 bar** and the specified hose internal \varnothing .

- **Precise, non-wearing cut-out clutch.**
- **High torque accuracy.**

Particularly suitable for series production screwdriving with quick-release bit holder for E 6.3 bits (see No. 674200 ff).

Oil-free - no additional pneumatic oiler required.

Spare part:

Selected service kits: Sets of replacement parts for most Atlas Copco pneumatic tools can be supplied on request for preventive maintenance and servicing.

Manufacturer's designation: S2450P

Torque range: 2.4 - 5 Nm

maximum screw \varnothing (8.8 - 12.9): M5

maximum speed: 1100 rpm

Tool arbor size: 1/4 inch

Format: Pistol

Technical description

recommended hose size (internal \varnothing)	10 mm
Manufacturer's designation	S2450P

maximum vibration to EN	< 2.5 m/s ²
maximum air consumption	360 l/min
Torque range	2.4 - 5 Nm
Format	Pistol
Weight	1.1 kg
Tool arbor size	1/4 inch
maximum screw Ø (8.8 - 12.9)	M5
Operating noise	78 dB(A)
maximum speed	1100 rpm
Compressed air connection	1/4 inch
Connection thread	BSW
Type of product	Screwdriver