



Pneumatic impact wrench 3/8 inch – 1/2 inch, Type: 7769



Order data

Order number	079202 7769
GTIN	015451779610
Item class	03R

Description

Version:

Robust impact wrench with **convenient one-hand changeover using Side-2-Side technology**, composite casing with thermal insulation properties and robust double hammer impact drive. Balanced weight distribution for more comfortable working. Exhaust air is directed downwards through the handle. **Tightening power can be regulated in steps.**

Torque range: 407 - 1464 Nm

Maximum screw \varnothing (8.8 - 12.9): M30

maximum speed: 7000 rpm

Tool arbor drive profile: Square

Tool arbor size: 3/4 inch

maximum air consumption: 882 l/min

Technical description

maximum vibration to EN	12.6 m/s ²
Tool arbor size	3/4 inch
Tool arbor drive profile	Square

Operating noise	97 dB(A)
Maximum screw Ø (8.8 - 12.9)	M30
maximum air consumption	882 l/min
maximum speed	7000 rpm
Weight	3.15 kg
Manufacturer's designation	7769
recommended hose size (internal Ø)	13 mm
Length	200 mm
Torque range	407 - 1464 Nm
Compressed air connection	3/8 inch
Connection thread	NPT
Type of product	Screwdriver