



Pneumatic impact wrench, Type: 6120



Order data

Order number	079204 6120
GTIN	015451729462
Item class	03R

Description

Version:

Impact wrench for the most demanding applications and highest torques. **Exceptionally robust 2-claw impact mechanism** (twin lobe) for a very long working life under rough conditions. The screw tightening phase starts slowly and increases with every impact. **Suitable for all bolt-tightening requirements.** Simple 3-piece design for **very low maintenance requirements.**

Torque range: 815 - 2710 Nm

Maximum screw Ø (8.8 - 12.9): M36

maximum speed: 3500 rpm

Tool arbor drive profile: Square

Tool arbor size: 1,1/2 inch

maximum air consumption: 1698 l/min

Technical description

Torque range	815 - 2710 Nm
Length	420 mm
Maximum screw Ø (8.8 - 12.9)	M36
recommended hose size (internal Ø)	13 mm
maximum speed	3500 rpm
Tool arbor size	1,1/2 inch

Weight	15.7 kg
Manufacturer's designation	6120
maximum air consumption	1698 l/min
Operating noise	102 dB(A)
maximum vibration to EN	21.8 m/s ²
Tool arbor drive profile	Square
Compressed air connection	1/2 inch
Connection thread	NPT
Type of product	Screwdriver