



## Pneumatic belt lisher Dynafiler®, Type: 15302



### Order data

Order number	079551 15302
GTIN	616026153028
Item class	03R

### Description

#### Version:

Versatile machines with **adjustable linishing belt guides, exactly true-running belts**, and with an exchangeable **contact arm** allowing the use of contact wheel or side face. The composite linishing belt coating enables **quick** and **easy change of the linishing belt**. The **linishing belt** cooling via the exhaust air prolongs the working life of the belts. Adjustable handle **Dynafiler® III, powerful 520 W** lisher for high removal rates, **surface preparation set, adjustable linishing head** with additional support handle. Linishing belt dimensions 6, 13, 19, 25×457 mm.

#### Application:

For abrading, deburring, blending, finishing and polishing, ideal also for flexible access to difficult places.

#### Supplied with:

Including the necessary coupling adaptors.

#### Note:

Other contact arm versions for Dynafiler® from No. 079559 available on request or in our eShop.

Packaging: Carrying case

Model range: Dynafiler III

Output power: 522 W

maximum speed: 20000 rpm

maximum air consumption: 906 l/min

Connection thread: NPT

Compressed air connection: 1/4 inch

## Technical description

Output power	522 W
Operating noise	87 dB(A)
maximum vibration to EN	< 2.5 m/s <sup>2</sup>
Tape width	6; 13; 19; 25; mm
Manufacturer's designation	15302
maximum air consumption	906 l/min
maximum speed	20000 rpm
Band length	457 mm
Weight	1.1 kg
Model range	Dynaflex III
Compressed air connection	1/4 inch
Connection thread	NPT
Packaging	Carrying case
Type of product	Finishing machine

## Accessories

Contact arm for Dynaflex® III Type 15350	079561 15350
Contact arm for Dynaflex® III Type 15357	079561 15357
Contact arm for Dynaflex® III Type 15321	079561 15321