



All-plastic cable drum G7, Type: 40B



Order data

Order number	081108 40B
GTIN	4003644001392
Item class	08B

Description

Version:

Generation 7 (G7) all-plastic cable drum. Increased stability, with HEDI DiagS diagnostic system, for continuous use outdoors. **3-year warranty**. Satisfies the specifications of DGUV I 203-006 (formerly BGI 608) and DGUV I 203-005 (formerly BGI 600).

The drum body and carrying frame are made of sturdy plastic for a high degree of safety. With ergonomically shaped carrying handle and large fold-away handle turning the drum, two-component Soft-Touch for greater comfort in use, cable guide and the well-proven HEDI rotation stop switch for locking the drum body. With 40 m HEDI PLUS H07BQ-F 3G 1.5 orange coloured armoured cable, cable embossed with "Hoffmann Group", Ø 290 mm, splash-proof socket insert with 4 Schuko sockets rated 250 V, plug seal lip, DiagS HEDI diagnostic system and thermal overload protection switch, protection class: IP44. For continuous use outdoors and on building sites / installation sites. Satisfies the requirements of BGI 608 and BGI 600, K2.

Function:

IP44: Protected against splashed water from all directions and protected against penetration by foreign bodies with $\emptyset > 1$ mm, however tools and wires should be kept away.

IP Index of Protection: IP 44

impact-resistant and splash-proof: Category 2 (K2) to BGI

Rated power unrolled: 3500 (16 A) W

Cable class: H07BQ-F Cable structure: 3G1.5



Material cable: Armoured cable

Cable length: 40 m Number of sockets: 4

Technical description

Material cable	Armoured cable
Rated power unrolled	3500 (16 A) W
impact-resistant and splash-proof	Category 2 (K2) to BGI
Cable class	H07BQ-F
IP Index of Protection	IP 44
Cable structure	3G1.5
Cable length	40 m
Number of sockets	4
Material of body	All-plastic
Power supply	Mains operated
Type of product	Cable drum