



### All-plastic cable drum G7, Type: 25B2



#### **Order data**

Order number	081133 25B2
GTIN	4003644022519
Item class	08B

## Description

#### **Version:**

Sturdy cable drum of high-impact plastic with thermal overload protection.

- · 400 V CEE input plug 16 A.
- · 400 V CEE output plug 16 A with spring-loaded cover.
- · Two 250 V standard Schuko sockets with spring-loaded covers.
- · Conductor cross-section 2.5 mm.

#### Certified for continuous exterior use and for use in humid environments.

Satisfies the specifications of DGUV I 203-006 (formerly BGI 608) and DGUV I 203-005 (formerly BGI 600).

#### **Function:**

IP44: Protected against splashed water from all directions and protected against penetration by foreign bodies with  $\emptyset > 1$  mm, however tools and wires should be kept away.

IP Index of Protection: IP 44

impact-resistant and splash-proof: Category 2 (K2) to BGI

Rated power unrolled: 5500 (16 A) W

Cable class: H07BQ-F Cable structure: 5G2.5

Material cable: Armoured cable

Cable length: 25 m



# **Technical description**

Cable structure	5G2.5
IP Index of Protection	IP 44
Cable length	25 m
Material cable	Armoured cable
Material of body	All-plastic
Cable class	H07BQ-F
impact-resistant and splash-proof	Category 2 (K2) to BGI
Rated power unrolled	5500 (16 A) W
Nominal voltage	400 V
Power supply	Mains operated
Type of product	Cable drum