



Safety cable reel, 250 V, Type: 17S



Order data

Order number	081192 17S
GTIN	7391390327543
Item class	08A

Description

Version:

Cable reel with **guided automatic draw-in and roll-up, with multiple stop points per revolution**. High-impact enclosed **plastic housing**. Thermal **overload cut-out**, sturdy H07RN-F neoprene cable with connection point.

Easy to mount on the wall or ceiling, with **180° pivoting range**.

Function:

IP44: Protected against splashed water from all directions and protected against penetration by foreign bodies with $\varnothing > 1$ mm, however tools and wires should be kept away.

Application:

Improved ergonomics by relieving cable tension, and for ensuring tidiness and avoiding the risk of accidents and injuries due to cables lying on the ground.

Note:

For spring return hose roll-up drums see No. 080078, 080079 and 080076.

impact-resistant and splash-proof: Category 2 (K2) to BGI

IP Index of Protection: IP 44

Rated power unrolled: 2400 W

Nominal voltage: 250 V

Length: 490 mm

Width: 190 mm

Height: 410 mm

Cable class: H07RN-F

Technical description

Width	190 mm
Rated power unrolled	2400 W
Cable structure	3G1.5
Material cable	Neoprene
Nominal voltage	250 V
Cable length	17 m
Height	410 mm
Length	490 mm
Cable class	H07RN-F
IP Index of Protection	IP 44
Power supply	Mains operated
Plug type, input	F
impact-resistant and splash-proof	Category 2 (K2) to BGI
Product name attribute	250 V
Type of product	Cable reel