

HEDI

Cable reel, 400 V / 16 A, Type: 20N



Order data

Order number	081197 20N
GTIN	4003644000487
Item class	08B

Description

Version:

Cable reel with **guided automatic draw-in and roll-up, with multiple stop points per revolution**. High-impact enclosed **plastic housing**. Thermal **overload cut-out**, sturdy H07RN-F neoprene cable with connection point.

Easy to mount on the wall or ceiling, with **150° pivoting range**.

Application:

Improved ergonomics by relieving cable tension, and for ensuring tidiness and avoiding the risk of accidents and injuries due to cables lying on the ground.

Note:

For spring return hose roll-up drums see No. 080078, 080079 and 080076.

impact-resistant and splash-proof: Category 2 (K2) to BGI

Rated power unrolled: 3000 (16 A) W

Nominal voltage: 400 V

Length: 361 mm

Width: 208 mm

Height: 450 mm

Cable class: H07RN-F

Technical description

Type	20N
------	-----

Cable length	20 m
Cable structure	5G1.5
Rated power unrolled	3000 (16 A) W
Body material	Plastic
Height	450 mm
Cable class	H07RN-F
Width	208 mm
Material cable	Neoprene
Length	361 mm
Nominal voltage	400 V
Power supply	Mains operated
impact-resistant and splash-proof	Category 2 (K2) to BGI
Product name attribute	400 V / 16 A
Type of product	Cable reel