



LED cordless work lamp, Power consumption: 26 W



Order data

Order number	081254 26
GTIN	5708997354414
Item class	08C

Description

Version:

Sturdy LED floodlight with shock-resistant aluminium casing and rubber protective edge.

- **Soft non-shadowing anti-glare lamp, with low heat emission.**
- **High light output, low energy consumption, long working life.**
- **Certified for exterior use and for use in humid environments.**

NOVA work lamps with integral carrying handle. High-performance COB-LED with 5-step dimmer function, pivoting. Due to the dual system, can be used both as a mobile cordless floodlight, and also with mains cable. Charge status display, remaining time display, dimmable in 5 stages.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Supplied with:

Including battery charger.

IP Index of Protection: IP 67

ATEX zone: no

Illumination: 300 - 3000 lm

Working life: 1 - 14 h

CRI value: 80

Number of rechargeable batteries contained: 1

Type of rechargeable battery: Lithium-ion

Technical description

Illumination	300 - 3000 lm
IP Index of Protection	IP 67
Power supply	Rechargeable battery-powered
Working life	1 - 14 h
ATEX zone	no
Colour temperature	6000 K
Battery voltage	11.1 V
Type of rechargeable battery	Lithium-ion
Battery capacity	4.4 Ah
Number of rechargeable batteries contained	1
Overall length	235 mm
Overall height	233 mm
Overall width	88 mm
CRI value	80
Weight	1780 g
Type of product	Work lamp

Accessories

Three-leg stand Height 1,35-3 m	081252 1,35-3
---------------------------------	---------------