

HEDI

LED floodlight with emergency light function, 230 V, Power consumption: 35 W



Order data

Order number	081269 35
GTIN	4003644000470
Item class	08B

Description

Version:

Non-shadowing and non-dazzle version with wide spread of light. **Dust-proof and splash –proof IP54.**

Robust work lamp with rubberised side parts and five different inclination angles depending on the positioning (90°, 35°, 25°, 15°, 0°). Integral carrying handle, on/off switch at the back. Approved for continuous use and on building sites/installation sites to BGI 608.

With 3 m connection cable H07RN-F3G1.5.

With emergency light function – switches the lamp on automatically in the event of a power failure - 21.6V/0.8Ah battery, up to 3 hours illumination, intelligent charging / discharging system.

Function:

IP54: Protected against splashed water from all directions and protected against penetration of dust into the inside (protected against dust), also completely protected against touching.

IP Index of Protection: IP 54

Illumination: 3850 lm

Working life: 3 h

Overall length: 273 mm

Overall width: 256 mm

Overall height: 163 mm

Connection cable length: 3 m

Technical description

Power consumption	35 W
Weight	2300 g

Illumination	3850 lm
Power supply	Mains-powered
Power supply	Rechargeable battery-powered
Beam dispersion angle adjustable	90 degrees
Beam dispersion angle adjustable	35 degrees
Beam dispersion angle adjustable	25 degrees
Beam dispersion angle adjustable	15 degrees
Beam dispersion angle adjustable	0 degrees
IP Index of Protection	IP 54
Working life	3 h
Nominal voltage	230 V
Overall width	256 mm
Overall length	273 mm
Overall height	163 mm
Connection cable length	3 m
ATEX zone	no
Product name attribute	230 V
Type of product	Area light