



Line Light work lamp, Type: 750

Order data

Order number	081340 750
GTIN	5708997000557
Item class	08C

Description

Version:

The Line Light work lamp is formed of an extruded acrylic profile with an **integral lens** (beam dispersion angle 75°). It is thus exceptionally **sturdy and shock-resistant**. It is thus designed for use under the **harsh conditions** and reliably provides strong and concentrated light in any working area. With **battery for mobile use** with additional torch on the end (150 lumen).

With 24 V DC input for direct connection to the machine or via transformer No. 081342 to the 230 V mains power supply.

The lamp can be rotated in its housing to give lighting without dazzle.

Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

Application:

For installation at the **workplace or in the vehicle**.

Supplied with:

Work light, 2 clips and fittings, end piece, cable entry / clamp, 2 connection sleeves.

IP Index of Protection: IP 67

Light output: 7 W

Illumination: 550 lm

Number of LEDs: 96

Overall length: 750 mm

Head Ø: 25 mm

Technical description

Power supply	Mains-powered
Illumination	550 lm
Number of LEDs	96

IP Index of Protection	IP 67
Lamp replaceable	no
Light output	7 W
Nominal voltage	230 V
Spread angle	75 degrees
ATEX zone	no
Head Ø	25 mm
Overall length	750 mm
Type of product	Workplace light

Accessories

Line Light cable, 8 m	081343
Transformer 24 V / 25 W	081342
Magnetic holder	081344
Sucker pad holder	081345